

## 8. Flat Bar to EN10025-2:2004 S275JR

Width mm	Thickness mm	3	5	6	8	10	12	15	20	25	30	40	50
10		A											
13		S	A	A									
16		S	A	A									
20		S	S	S	S	S	A						
25		S	S	S	S	S	A	A	A				
30		S	S	S	S	S	S	A	A	A			
35		A	A	A	A	A	A	A					
40		S	S	S	S	S	S	A	A	A	A		
45		A	A	A	A	A	A	A	A	A	A		
50		S	S	S	S	S	A	S	A	A	A	A	
60		A	S	S	S	S	A	A	A	A	A	A	
65			A	A	A	A	A	A	A	A	A	A	A
70			A	S	S	S	A	A	A	A	A	A	
75		A	A	S	A	A	A	A	A	A	A		
80		A	A	S	S	S	A	A	A	A	A	A	A
90			A	A	A	A	A	A	A	A	A		
100		A	S	S	S	S	A	S	A	A	A	A	A
110			A	A	A	A	A	A	A	A	A		
120			A	S	S	S	A	A	A	A	A		
130			A	S	S	S	A	A	A	A	A		
140				A	A	A	A	A	A	A	A		
150		A	S	S	S	S	A	S	A	A	A	A	A
160						A	A	A	A	A			
180				A	A	A	A	A	A	A	A	A	A
200				S	S	S	S	A	A	A	A		
220				A	A	A	A	A	A	A	A		
250				S	S	S	A	A	A	A	A		
300				S	S	S	A	A	A	A	A		
350						A	A	A	A	A	A		
400						A	A	A	A	A	A		
450							A	A	A	A			

S = Stock item

A = Available as a B2B Sale